7

loop haptic has at its end a knob or protuberance 110 somewhat similar to that shown in FIG. 8A. The loop haptics extend into the periphery of the bag between the anterior remnant and the posterior capsule to fixate the haptics and prevent movement of the knobs through fibrosis-defined 5 tunnels defined about the loops. FIGS. 13 and 14 illustrate respectively the correct manner for the loop haptic to be oriented to engage the bag periphery wherein a portion of the loop and the knob engage the bag periphery. FIG. 14 shows an undesirable disposition of the loop haptic and knob in the 10 fibrosis which does not provide optimum and desirable engagement with the bag periphery.

FIG. 15 illustrates an embodiment which is similar to that of FIGS. 12 and 13 except that a plurality of knobs or protuberances 110, similar to that of FIG. 8A, are positioned ¹⁵ in spaced relation along the loop haptics to provide improved fixation of the loop haptic in the peripheral cul-de-sac of the bag.

FIGS. 16 and 16A show an embodiment having a haptic comprising two half disk-shaped members 112 from which extend a plurality of loop haptic portions 114. The edge of the disk-shaped portions and the loops are adapted to fit in the peripheral portion of the bag between the capsular remnant and the posterior capsule to fixate the haptic.

FIGS. 17 and 17A illustrate an embodiment which has a disk haptic portion 116 on which are mounted and from which extend a plurality of filament haptic portions 118 of generally arcuate configuration at the end of each of which is disposed a knob or protuberance 120. The loop haptic portions and the knobs serve the purposes outlined relative to embodiments earlier described.

FIG. 18 is an embodiment having a disk haptic 124 wherein are integrally formed peripheral inclined prong portions 126 extending somewhat tangentially with knobs at the ends thereof adapted to fit within the periphery of the bag between the anterior capsular remnant and the posterior bag for engagement with the periphery for the formation of fibrosis thereabout for the purposes earlier described.

FIG. 19 is an embodiment having a disk haptic 130 on the 40 periphery of which are disposed a plurality of knobs 132, such as the knobs of FIG. 28, to serve the purposes earlier described in relation to other embodiments.

FIG. 20 is an embodiment having a disk haptic 134 with a plurality of circular openings 136 defined in its distal ⁴⁵ peripheral portion, the haptic periphery and these openings become engaged with fibrosis to serve the purposes earlier described.

FIG. 21 shows an embodiment similar to that of FIG. 20, with slot-shaped openings 138 defined in disk haptic 140.

FIG. 22 is somewhat similar to the embodiments of FIGS. 19 and 21, and has slot-shaped openings 138 interspersed with knobs 140 in its disk peripheral edge portion.

FIG. 23 shows an embodiment wherein disk haptic portions 141 extend outwardly from an optic, and extending from their distal edge portions are a plurality of flexible loop haptic elements 143 with protuberances 145 thereon for engagement in the peripheral edge portion of the capsular bag for fixation of the haptic and centration of the optic.

FIGS. 24 and 25 show embodiments each having four plate haptics 142 extending from and equispaced about an optic 144, and having defined in their peripheral portions slot-shaped openings 145, the haptic edge portion and the openings being extensible in the bag periphery for purposes 65 earlier described; the embodiment of FIG. 25 has similarly equispaced haptics extending from an optic 148, each haptic

8

having a plurality of knobs like those of FIG. 29 on its peripheral portion, the knobs and haptic edge portions serving the purposes earlier described.

The FIG. 26 embodiment is similar to the embodiment of FIGS. 24 and 25, with an optic 150 having four equispaced haptics 152 extending therefrom, each having slot-shaped openings 154 therein and a knob 156 thereon.

FIGS. 27 and 28 illustrate embodiments wherein platetype haptics extend oppositely from optic 160 in FIG. 27, and from optic 162 in FIG. 28, the FIG. 27 embodiment having a haptic with slot-shaped openings 164 in its distal portion, and the haptics (lower one not shown) of FIG. 28 having a plurality of knobs 166 in its peripheral portion, the slots and the knobs serving the purposes earlier described.

FIG. 29 is a partial sectional view taken at line 29—29 in FIG. 28, and

FIG. 30 is a partial sectional view taken at line 30—30 in FIG. 27.

Thus there have been shown and described novel intraocular lenses with fixated haptics which fulfill all the objects and advantages sought therefor. Many changes, modifications, variations and other uses and applications of the subject invention will, however, become apparent to those skilled in the art after considering this specification together with the accompanying drawings and claims. All such changes, modifications, variations and other uses and applications which do not depart from the spirit and scope of the invention are deemed to be covered by the invention which is limited only by the claims which follow.

What is claimed is:

1. An intraocular lens for implanting within a natural capsular bag of a human eye, said lens implant comprising:

- a lens body having anterior and posterior sides and including an optic and two or more plate haptics spaced about said optic, said haptics having inner ends adjacent said optic and outer ends extending from said optic;
- a plurality of protuberances extending outwardly from at least one of the anterior and/or posterior sides of one or more of said haptics to fixate said haptic in a natural capsular bag of an eye; and
- at least one of said haptics has a plurality of openings formed therethrough to allow fibrosis of an anterior capsule remnant to a posterior capsule remnant through said haptic outer end opening following implantation of said lens into a natural capsular bag of an eye.
- 2. An intraocular lens for implanting within a natural capsular bag of a human eye, said lens implant comprising:
 - a lens body having anterior and posterior sides and including an optic and haptics spaced about said optic, said haptics having inner ends adjacent said optic and outer ends extending from said optic;
 - said haptics comprise a plurality of four plate haptics, wherein said haptic outer ends have a width greater than the width of said haptic inner ends; and
 - at least one of said haptics has a plurality of protuberances extending outwardly from at least one of the anterior and/or posterior sides of said at least one haptic to fixate said haptic in a natural capsular bag of an eye.
- 3. An intraocular lens for implanting within a natural capsular bag of a human eye, said lens implant comprising,
 - a lens body having anterior and posterior sides and including an optic and haptics spaced about said optic, said haptics having inner ends adjacent said optic and outer ends extending from said optic;